



Features:


- Provides better light on areas need more illuminance
- Our patented hook and the radiator can make it easy to install and keeps heat from damaging the lamp components.
- Energy Saving last to zero 50000 hours life space

Application


Factories, Warehouses, Gymnasium, Indoor Playgrounds, and other indoor lighting Applications

Technical Specifications

Outline Drawing



Polar Candela Distribution



Illuminance

Center Beam LUX	Beam Width	
	1.9m	3.7m
1,093.51 LUX	1.9m	1.9m
273.38 LUX	3.7m	3.7m
121.50 LUX	5.6m	5.6m
68.34 LUX	7.5m	7.4m
43.74 LUX	9.3m	9.3m
30.38 LUX	11.2m	11.1m

■ Vert. Spread: 70.1° ■ Horiz. Spread: 69.6°

Ordering Guide

Photo	Odering No.	Power	Product Name	CCT	Lumens	Description
	A-6880-P06-CQ5H	10W	UFO-6 Factory Light	5500K	642	Number of LED: 6 Cree Chips Input Voltage: 220V/50Hz Temperature Range: -40 ° C to 45 ° C Dimensions: 380mm Dia. X 362mm H
	A-6880-P12-CQ5H	20W	UFO-12 Factory Light	5500K	1284	Number of LED: 12 Cree Chips Input Voltage: 220V/50Hz Temperature Range: -40 ° C to 45 ° C Dimensions: 380mm Dia. X 362mm H
	A-6880-P36-CQ5H	50W	UFO-36 Factory Light	5500K	3852	Number of LED: 36 Cree Chips Input Voltage: 220V/50Hz Temperature Range: -40 ° C to 45 ° C Dimensions: 380mm Dia. X 362mm H

Packing Information

Dealer Information

